

Arrow Lock MK Series Entry Ball Knob Lock Brushed Chrome Finish - 2-3/8in Backset - Keyway: AR1 - MK11BD26D-300-111



ar_mk11bd.png



Rating: Not Rated Yet

Price

Price Each:\$112.06

[Ask a question about this product](#)

Description

Arrow Lock MK Series Entry Ball Knob Lock Brushed Chrome Finish - 2-3/8in Backset - Keyway: AR1 - MK11BD26D-300-111

SKU: MK11BD26D-300-111

Arrow MK Series offer the Security Professional simple solutions to accessibility requirements. Their clean designs, architectural finishes and available functions make them ideal for commercial applications where heavy duty grade one hardware may not be necessary.

Certification

- ANSI/BHMA A156.2, Series 4000, Grade 2
- Federal Specifications FF-H-106C, Series 160

Features

- Function: MK11 F109 (F81 & F82)/161A, 160A. Entrance/Office, Dead locking latch bolt operated by knob from either side except when outside knob is locked by pushing turn button inside. Key outside or operating inside knob releases turn button unlocking outside knob except when turn button has been rotated to keep outside knob locked. Inside turn button must be manually operated to unlock outside knob. Inside knob always operates latch bolt.
- Design: Ball BD
- Finish: 626 US26D 26D Satin Chromium Plated
- Backset: 2-3/8" (60.32mm) standard.
- Latch: Brass with 1/2" (12.7mm) throw Latch housing is steel, with zinc dichromate finish for corrosion resistance 7/8" (22.225mm) bore in edge of door is required
- Latch Front: Brass, bronze or stainless steel. Standard faceplate for 2-3/8" (60.32mm) backset measures 2-1/4" (57.15mm) x 1" (25.40mm) with a flat front
- Strike: Brass, bronze or stainless steel. Standard "T" strike measures 2-3/4" (69.85mm) x 1-1/8" (28.57mm). All strikes have a 1-1/4" (31.75mm) lip to center dimension.

- Handing: Reversible
- Door Thickness: 1-3/8" (34.92mm) to 1-3/4" (44.45mm)
- Lock Chassis: Cold rolled steel with zinc dichromate finish for corrosion resistance Requires standard 2-1/8" (53.97mm) bore through door
- Cylinder: Solid brass 6 pin cylinder with Arrow "A" keyway, keyed to 5 pins. Supplied with two 5 pin brass keys