Arrow Lock CL Series Entry Solar Lever Lock Polished Brass Finish - SC1 Keyway - Adjustable Backset - CL11SC03-502-511-CS



ar_cl11sc605.png



Rating: Not Rated Yet **Price**Price Each:\$83.51

Ask a question about this product

Description

Arrow Lock CL Series Entry Solar Lever Lock Polished Brass Finish - SC1 Keyway - Adjustable Backset - CL11SC03-502-511-CS

SKU: CL11SC03-502-511-CS

Arrow C Series offer exceptional value and quality to meet demands of single and muti-family housing markets.

Certification

• ANSI A156.2, Series 4000, Grade 2

Features

- Function: CL11 Entry Latchbolt operated by lever from either side except when inside turn button locks outside lever. When outside lever is locked, Latchbolt operated by key outside or turning inside lever. inside button must be manually released.
- Design: Solar SC
- Finish: 605 US3 03 Polished Brass
- Backset: Adjustable 2-3/8" (60.32mm) or 2-3/4" (70mm) standard.
- Latch: 1/2" (12.7mm) throw. Latch housing is steel, with zinc dichromate finish for corrosion resistance. 1" bore in edge of door is required
- Latch Front: Brass. Supplied standard with 1" x 2-1/4" (25mm x 57mm) square corner, 1" x 2-1/4" round corner, and 1-1/8" x 2-1/4" (29mm x 57 mm) square corner latch fronts
- Strike: Brass, bronze or stainless-steel. Standard "Full lip" strike measures 1-5/8" x 1-1/4" (41mm x 57 mm).
- · Handing: Reversible
- Door Thickness: 1-3/8" (34.92mm) to 1-3/4" (44.45mm)
- Lock Chassis: Tubular chassis. Cold rolled steel with zinc dichromate finish for corrosion resistance Requires standard 2-1/8" (53.97mm) bore through door

• Cylinder: Solid brass 6 pin cylinder with Schlage "C" keyway, keyed to 5 pins. Supplied with two 5 pin brass keys