

E-Plex E5010 Electronic Access Control Exit Device Operator- Key Override- Medeco/Yale-Trim - Statin Chrome - E5010-M-WL-626-41



ka_e5010mwl626.png

Rating: Not Rated Yet

Price

Price Each:\$977.29

[Ask a question about this product](#)

Description

E-Plex E5010 Electronic Access Control Exit Device Operator- Key Override-Medeco/Yale-Trim - Statin Chrome - E5010-M-WL-626-41

SKU: - E5010-M-WL-626-41

- [Overview](#)
- [Features](#)
- [Technical Data](#)

- The E-Plex 5000 Electronic Pushbutton Lock Series provides exterior access by combination, while allowing free egress. This electronic pushbutton lock eliminates problems and costs associated with issuing, controlling, and collecting keys and cards, has up to 100 Access Codes and is programmed via keypad or with optional Microsoft Excel-based software.

- No Wires: No Wires: E-Plex's LectroBolt eliminates running wires to or through the door-no risk of damage from pinched wires that can result in costly callbacks

Locking Device: Cylindrical latch with 3-hour UL/ULC fire rating on "A" labeled doors

Exit Device Compatibility: Exit Trim-Use only for:

Arrow S1250

Arrow S3883F/S3800

Black & Decker (K-2) QED111/112

Cal Royal 9800

Cal Royal 2200

Corbin Russwin ED5200/5200A

Detex 1001 BP1

Detex 10/F10 Series

Dorex 8500R/8500F

Dorex 9500PR/9500FR

Dorma 9300/F9300

Monarch 18R*, F18R*

*(requires special K-Hub Adapter)

Precision 21/FL21

Sargent 2828

Sargent 3828

Sargent 8810E/8800

Sargent 8888

Von Duprin 22/22F

Von Duprin 98/98F

Von Duprin 99/99F

Von Duprin XP98/99

Yale YME2100/2100

Yale 7100

Number of Codes: 100 access codes per door (upgrade to 300 via software); over 100 million possible code combinations

Audit Trail: The most recent 9,000 lock events are recorded in memory, including the use of mechanical key override. Software is required to view audit events.

Programming: Locks are programmed via E-Plex Enterprise Software (not included)-provides easy management of doors and users. Upgradable to wireless.

Handing: Non-handed

Key Override: Removable Cores: Large format-Medeco/ASSA/Yale/Abloy (5 or 6-pin length); ; core not included

Lock Function Customization: Locks are easily customized on site via keypad to work as various BHMA lock functions, eliminating the requirement to stock multiple locks for different applications. Built-in options include: Entry, Privacy, and Residence lock, (thumb turn required for privacy and residence functions)

Operation Modes:

PIN access

Passage-can be toggled on/off or can be pre-programmed to re-lock after a certain number of hours

Lockout

Authority Levels: Five (5) different levels allow who has access to specific lock functions, including:
Master Level - performs all set-up and programming functions

Manager Level - administers common programming functions

Access User Level - entry granted with valid PIN

Service Level - codes for single event or single day access, programmable in advance

Maintenance Level - no access is granted, information can be uploaded/downloaded to/from the lock

User Parameters:

Code length - adjustable to accept 4 to 8 digits

Anti-tamper lockout - adjustable from 3 to 9 invalid attempts with an adjustable period of 0 to 90 seconds

Re-lock time - adjustable from 2 to 20 seconds

Lock Power: Battery Powered - Batteries located in interior housing cover; offers quick and easy battery replacements (Four AA Alkaline batteries provide up to 180,000 cycles); lock data is maintained if batteries fail

- Construction: Extra heavy-duty cylindrical lockset, solid cast housings, solid cast levers, cylindrical drive wear tested for extensive use in indoor and outdoor applications

Door Preparation: Cylindrical and Exit Trim-ASA 161 (Easily installs on door preparation with two additional through bore holes (wood or metal doors)

Door Thickness: E-Plex 5000 Exit Trim-1 3/4" (44 mm) to 2 1/4" (57 mm) Pre-assembled to accommodate doors 1 5/8" (41 mm) to 2" (50 mm)

Numeric Keypad: Vandal resistant, solid metal pushbuttons
Handing: Non-handed

Backset: Varies by exit device/div>

Strikes: Supplied with exit device

Minimum Stile Recommended: 5" (127 mm)

Strike: Exit Device Strike: Supplied with Exit Device

Key Cylinder: Prepped for Medeco Removable core: cylinder not included

Accessibility Standard: Americans with Disabilities Act (ADA)

Durability: ANSI/BHMA A156.3, A156.25; Grade 1 Certified

Environmental: Indoor/Outdoor approved; Front Housing: -31 ?F (-35 ?C) to 151 ?F (66 ?C)

Fire Rating: 3-hour UL/ULC fire rating for "A" labeled doors

Warranty: 3-year warranty from date of installation; built-in warranty counter in lock memory

Standard Finishes: Satin Chrome 26D (626)

Items Supplied: Includes Lock assembly, installation manual, full-scale template, quick reference guide, operations manual, and required installation hardware; Exit Device and mounting hardware not included

Weight 9.5 lbs. (4.3 kg)