Ilco Speed 044 Lever Operation (Semi-Automatic) Key Machine



speed_044_left.png



Rating: Not Rated Yet **Price**Price Each:\$2.012.23

Ask a question about this product

Description

Ilco Speed 044 Lever Operation (Semi-Automatic) Key Machine

SKU: - IL SPEED 044

- Overview
- Features
- Technical Data
- The Speed 044 is designed for duplicating edge cut automotive, residential and commercial keys. The semi-automatic design allows the operator to duplicate keys with speed and accuracy.

Once keys are loaded, the spring loaded carriage is engaged by the press of a button. The lever is then moved manually to control the carriage movement during the cutting cycle. The Speed 044 Semi-Automatic is loaded with features that any user will readily appreciate

- The spring loaded carriage is engaged by the press of a button and applies a consistent cutting pressure while in automatic mode
 - ? Four sided, nickel plated jaws for clamping the majority of all edge cut/flat type keys. Smooth rotation by simply twisting into position.
 - ? Slotted jaw surfaces accommodate tip stop bars and a rigid shoulder gauge design to allow for greater accuracy when loading and gauging keys
 - ? Wide spacing 3 1/2? (88.9 mm) spacing between clamps accommodate large bow (head) and long blade keys, including flip style keys
 - ? Depth tracer system with micro adjustment for precise calibration in increments of .00098? (0.025mm)
 - ? TiN (Titanium Nitride) coated cutter for longer life and oxidation resistance

- ? Nylon deburring brush
- ? Electro-magnetic ?main? safety switch with a separate cutter motor switch for easy access.
- ? Large transparent cutter safety shield contains chips and provides a storage area for accessories
- ? Large drawer-type swarf (chip) tray under the carriage for easy access
- ? Mounting bracket included for securing the machine to counter
- ? Two year warranty
- Power Supply: 120V-60Hz, Rated Current 4.1 Amps

Maximum absorbed power: 2.8 Amp, 200 Watt Cutter motor: single phase and speed

Tool Speed: 1350 rpm

Cutter: BC0599XXXX TiN coated HSS

Cutter Guide: BJ1161XXXX

Brush: BJ0929XXXX 3/8" (10mm) Nylon

Width: 22.8" (580mm)

Depth: 18.1" (460mm)

Height: 9.8" (250mm)

Weight: 31 lbs. (14 kg)