National Lock C8060 Disk Tumbler Cam Lock 1-3/4" Keyed Different - NL C8060-KD-14A



Rating: Not Rated Yet **Price** Price Each:\$12.37

Ask a question about this product

Description National Lock C8060 Disk Tumbler Cam Lock APPLICATION ? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 1-7/16" CYLINDER LENGTH - 1-3/4" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING ? Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH -Bright Nickel PACKAGING ? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately. National Lock C8060 Disk Tumbler Cam Lock APPLICATION ? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 1-7/16" CYLINDER LENGTH - 1-3/4" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING ? Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH - Bright Nickel PACKAGING ? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately. National Lock C8060 Disk Tumbler Cam Lock APPLICATION ? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 1-7/16" CYLINDER LENGTH - 1-3/4" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING ? Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH - Bright Nickel PACKAGING ? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately. National Lock C8060 Disk Tumbler Cam Lock APPLICATION ? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 1-7/16" CYLINDER LENGTH - 1-3/4" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING ? Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH - Bright Nickel PACKAGING ? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately. National Lock C8060 Disk Tumbler Cam Lock APPLICATION ? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 1-7/16" CYLINDER LENGTH - 1-3/4" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING ? Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH - Bright Nickel PACKAGING ? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately.