## National Lock C8073 Disk Tumbler Cam Lock 1-3/16" Master Keyed & Keyed Different - NL C8073KKD-14A



Rating: Not Rated Yet **Price**Price Each:\$12.13

Ask a question about this product

Description National Lock C8060 Disk Tumbler Cam Lock APPLICATION ? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 7/8" CYLINDER LENGTH - 1-3/16" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING? Master Keyed and Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH - Bright Nickel PACKAGING? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately. National Lock C8060 Disk Tumbler Cam Lock APPLICATION? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 7/8" CYLINDER LENGTH - 1-3/16" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING ? Master Keyed and Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank, FINISH - Bright Nickel PACKAGING? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately. National Lock C8060 Disk Tumbler Cam Lock APPLICATION ? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 7/8" CYLINDER LENGTH - 1-3/16" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING? Master Keyed and Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH - Bright Nickel PACKAGING? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately. National Lock C8060 Disk Tumbler Cam Lock APPLICATION? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 7/8" CYLINDER LENGTH - 1-3/16" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING ? Master Keyed and Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH - Bright Nickel PACKAGING? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately. National Lock C8060 Disk Tumbler Cam Lock APPLICATION ? For drawers, R.H. or L.H. doors with lipped/overlay construction (straight cam) or flush construction (formed cam). For overlay application, the combined thickness of front and frame cannot exceed the cylinder length. MAX MATERIAL THICKNESS - 7/8" CYLINDER LENGTH - 1-3/16" OPERATION ? 90? cam turn on all locks. Key removable in both locked and unlocked positions. KEYING? Master Keyed and Keyed Different. Will key together with all other disc tumbler locks using D8785 key blank. FINISH - Bright Nickel PACKAGING? Supplied with two keys, trim washer, spur washer (for wood), mounting nut, two cams and two stop washers. If flat washer (for metal) is needed, order C2015-2C separately.