


National Lock C8173 7/8" Pin Tumbler Door Lock Keyed Alike to #915 26D Finish - NL C8173-915-26D



nl_c8173.png



Rating: Not Rated Yet

Price

Price Each:\$36.73

[Ask a question about this product](#)

Description National Lock C8173 pin tumbler door locks equipped with Advantage +Plus. 7/8" Cylinder length, 3/4" bolt travel. The PLUS feature allows you to remove the cylinder from our pin tumbler box locks while the lock remains in place. No mounting screws need to be removed. Simply use a 5/64" Allen wrench from the back to remove the cylinder and plug for re-keying. APPLICATION ? For R.H. or L.H. doors. Surface mounted. Requires 57/64" diameter hole for cylinder. OPERATION ? Key removable in both locked and unlocked positions. KEYING ? Keyed Alike to Key # 915. Will key together with all other pin tumbler locks using D4291 key blank except Mail Bx locks. See table for available keying. Master keying to GM1 is available as special order. PACKAGING ? Supplied with two keys, strike and mounting screws. If trim ring is required, order C2017 separately. National Lock C8173 pin tumbler door locks equipped with Advantage +Plus. 7/8" Cylinder length, 3/4" bolt travel. The PLUS feature allows you to remove the cylinder from our pin tumbler box locks while the lock remains in place. No mounting screws need to be removed. Simply use a 5/64" Allen wrench from the back to remove the cylinder and plug for re-keying. APPLICATION ? For R.H. or L.H. doors. Surface mounted. Requires 57/64" diameter hole for cylinder. OPERATION ? Key removable in both locked and unlocked positions. KEYING ? Keyed Alike to Key # 915. Will key together with all other pin tumbler locks using D4291 key blank except Mail Bx locks. See table for available keying. Master keying to GM1 is available as special order. PACKAGING ? Supplied with two keys, strike and mounting screws. If trim ring is required, order C2017 separately. National Lock C8173 pin tumbler door locks equipped with Advantage +Plus. 7/8" Cylinder length, 3/4" bolt travel. The PLUS feature allows you to remove the cylinder from our pin tumbler box locks while the lock remains in place. No mounting screws need to be removed. Simply use a 5/64" Allen wrench from the back to remove the cylinder and plug for re-keying. APPLICATION ? For R.H. or L.H. doors. Surface mounted. Requires 57/64" diameter hole for cylinder. OPERATION ? Key removable in both locked and unlocked positions. KEYING ? Keyed Alike to Key # 915. Will key together with all other pin tumbler locks using D4291 key blank except Mail Bx locks. See table for available keying. Master keying to GM1 is available as special order. PACKAGING ? Supplied with two keys, strike and mounting screws. If trim ring is required, order C2017 separately.