

Trine 4100-32D -Flexible Strike, 3 Hour Rating 12-24 AC / DC, 32D Finish



tr_4100_with_4_fp.png



Rating: Not Rated Yet

Price

Price Each:\$472.24

[Ask a question about this product](#)

Description

Trine 4100-32D -Flexible Strike, 3 Hour Rating 12-24 AC / DC, 32D Finish

SKU: - TR 4100-32D

- [Overview](#)
- [Features](#)
- [Technical Data](#)

- The Trine 4100 Electric Strike has 1 - 3/8" Shallow backset and Three Hour Fire Rated. included are the 4 most used faceplates to make specifying and installing easy. Covers 90%+ of Cylindrical & Mortise Lock configurations (without deadbolt), plus faceplates can be kept & used to help accomodate for door sag.

Application: Most installations with cylindrical locks and deadlatches

Designed to work with: Schlage "L" Series and Yale 8700 Series without relocating the mounting tabs

PoE Friendly

- Durability: 1,000,000 Life Cycles

Action: Fail secure standard (unlocks with power).

Grade: BHMA Grade 1 Electric Strike.

Handing: Non Handed

- Electric Characteristics:
Voltage: 12-24VAC/DC

Amps:

12VDC - 0.240 AMPS

24VDC - 0.114 AMPS

12VAC - 0.210 AMPS

16VAC - 0.280 AMPS

24VAC - 0.420 AMPS

Ohms:

12VDC - 50.0

24VDC - 210.0

12VAC - 50.0

16VAC - 50.0

24VAC - 50.0

Duty: AC - Intermittent (Buzzing)DC - Intermittent /Continuous (Silent)

Lead Colors:

16VAC - Red/blue

24VAC - Red/blue

12VDC - Red/blue

24VDC - brown/Red

12VAC - Red/blue

Latch Length: For use with locksets having up to 5/8" throw

Dimensions:

Face Plate: 4-7/8" x 1-1/4"

Mortise Backset: 1-3/8"

Cavity Offset: Based on face plate -None - Centered, 19/32", 29/32" or 11/64"

Cavity Depth: 3/4"

Cavity Width: 25/32"

Cavity Height: 1-3/8" to 3-1/4" based on Face plate

Finish: Stainless Steel 32D

Specifications:

Class A, 3 Hour fire rated single door / frame configuration

WH recognized for UL10C, Fire Tests of Door Assemblies

UBC 7-2, Uniform building Code

CAN4 S104, Standard Method for Fire Tests of Door Assemblies

NFPA 252 - Issue: 1999/01/01 Standard Methods of Fire Tests of Door Assemblies

NOTE: WH fire listing is void when using fail safe action.

UL® Listed 1034: Burglary Resistant

UL294 (6th Edition) listed

ANSI/BHMA A156.5 - 1992 - 4-7/8" x 1-1/4" Fits