

Trine 4200-Alum Flexible Strike, 12-24 AC / DC, Aluminum Finish



tr_4200.png

Rating: Not Rated Yet

Price

Price Each:\$188.09

[Ask a question about this product](#)

Description

Trine 4200-Alum Flexible Strike, 12-24 AC / DC, Aluminum Finish

SKU: - TR 4200-ALUM

- [Overview](#)
- [Features](#)
- [Technical Data](#)

- Application: Most installations with cylindrical locks and deadlatches

Designed to work with: New or replacement, aluminum or hollow, metal jamb latch installations

PoE Friendly

- Action: Fail secure standard (unlocks with power).

Grade: BHMA Grade 1 Electric Strike.

Handing: Non Handed

- Electric Characteristics:
Voltage: 12-24VAC/DC

Amps:

12VDC - 0.240 AMPS

24VDC - 0.114 AMPS

12VAC - 0.210 AMPS

16VAC - 0.280 AMPS

24VAC - 0.420 AMPS

Ohms:

12VDC - 50.0

24VDC - 210.0

12VAC - 50.0

16VAC - 50.0

24VAC - 50.0

Duty: AC - Intermittent (Buzzing)DC - Intermittent /Continuous (Silent)

Lead Colors:

16VAC - Red/blue

24VAC - Red/blue

12VDC - Red/blue

24VDC - brown/Red

12VAC - Red/blue

Latch Length: For use with locksets having up to 5/8" throw, based on 1/8" door gap.

Dimensions:

Face Plate: 4 included - Length 4-7/8", 4-7/8 RC, 6-7/8", 7-15/16"; all width 1-1/4"

Mortise Backset: 1-1/16"

Cavity Offset: None - Centered

Cavity Depth: 1/2"

Cavity Width: 25/32"

Cavity Height: 1-3/4" to 2-13/16" based on face plate

Finish: Aluminum

Specifications:

UL® Listed 1034: Burglary Resistant

UL294 (6th Edition) listed