

Trine EN400-32D-LH Outdoor Strike, 24VDC, 32D Finish



tr_en400_lh.png

Rating: Not Rated Yet

Price

Price Each:\$391.40

[Ask a question about this product](#)

Description

Trine EN400-32D-LH Outdoor Strike, 24VDC, 32D Finish

SKU: - TR EN400-32D-LH

- [Overview](#)
- [Features](#)
- [Technical Data](#)

- Application: OutdoorUL® rating allows the strike to be used anywhere - especially good for gates.

Designed to work with: Schlage L Series, Sargent 7700, 8100, & Yale 8700

- Durability: 1,000,000 Life Cycles

Action: Fail secure/Fail safe field reversible on DC units.

Grade: BHMA Grade 1 Electric Strike -- Contains a one piece locking mechanism with one Solenoid -- less parts mean less problems.

Handing: Left Hand - field reversible

- Electric Characteristics:

Voltage: 24VDC

Amps: 0.150

Ohms: 164.0

Electric Strikes: Trine EN400-32D-LH Outdoor Strike, 24VDC, 32D Finish

Duty: Intermittent /Continuous (Silent)

Lead Colors: Black/white

Latch Length: Use with cylindrical locksets, mortise locks without dead bolts, and mortise exit devices with up to 7/8" throw.

Dimensions:

Face Plate: 4-7/8" x 1-1/4"

Mortise Backset: 1-11/16"

Cavity Offset: None - Centered

Cavity Depth: 1"

Cavity Width: 7/8"

Cavity Height: 1-1/2"

Latch Shim Kit provided for horizontal cavity adjustment.

Finish: Stainless Steel 32D

Specifications:

UL® Listed 10C: Fire-rated - Class A, 3-hour, single swing door

UL® Listed 1034: Indoor/Outdoor Burglary Resistant

UL294 (6th Edition) listed

BHMA: BHMA 156.31 2001, Grade 1

NYC: NYC MEA 79-01-E